

Light Truck Battery



Function introduction

Acquisition function: single voltage, temperature, current, total voltage acquisition; measurement range of single battery voltage: 0 <UD <5V; temperature measurement range: -40~125°C.

It has the function of voltage detection, total voltage of lithium battery pack, and charge / discharge current detection. It has the SOC estimation function.

Protection function: after temperature, single voltage, total voltage, and current exceed the protection threshold.

Have the function of resting position.



Matters need attention

warn!

Never put your batteries in the fire, heat them, or store them in an environment above the temperature specified in the specification.

Do not attach the positive and negative extremes to the charger or device.

It is forbidden to contact the positive and negative poles of the batteries with a wire or any metal (such as a necklace or a hairpin). If so, these batteries are transported and stored together, which may cause a short circuit.

Do not hammer or step on the battery, and use no other ways to strike the battery.

Do not dismantle or change the external structure of the battery.

Never soak your batteries in water or wet them.

pay attention to!

When the battery runs up, please charge it promptly (after 15 days).

The battery should be charged with the original charger, and according to the correct operation instructions, the voltage, temperature and other batteries are within the prescribed range, so as to ensure the safe and effective use of the battery.

Please stop using the battery in abnormal conditions such as odor, discoloration, noise, leakage, and serious deformation.

When the electrolyte leaks into the skin and eyes, please rinse with water and see a doctor immediately.

Please place the battery beyond the pet and the child, and prohibit the child from touching the battery.

The battery pack is prohibited to be used in series. If you need a series application, please contact the manufacturer for consultation.

The battery pack is prohibited to be used in parallel. If you need a series application, please contact the manufacturer for consultation.

The battery should be stored at room temperature and should be charged to 40% to 60% of the electricity. To prevent the battery from going down, charge every month.

The battery should be used under the specified conditions and not stored for more than 3 months.

For batteries stored for more than a year, performance is not guaranteed.

System parameters

| order number | project | characteristic |
|--------------|-------------------------------------------|---------------------------------------------------|
| 1 | Rated capacity (Ah) | 173 |
| 2 | Rated energy (k wh) | 101.8 (4 boxes as system) |
| 3 | nominal voltage (V) | 588.8 |
| 4 | Single standard box size (mm) | 1245*465*242 |
| 5 | weight (Kg) | ≈732 |
| 6 | Charging stop voltage (V) | 671.6 |
| 7 | Discharge cut-off voltage (V) | 460 |
| 8 | Rated Charge current (A) | 150 |
| 9 | Rated discharge current (A) | 170 |
| 10 | 30s discharge current (A) | 255 |
| 11 | communication | CAN communication |
| 12 | Charge and discharge with different mouth | The same mouth |
| 13 | levels of protection | IP67 |
| 14 | working temperature (°C) | Charging charge: 0~60 Discharge supply: -30~60 |
| 15 | Storage temperature: (°C) | 0~45 |
| 16 | shipment SOC | 30%~50% |
| 17 | cycle life | ≥3500 @25°C |

Protection parameters

| order number | project | content | acceptance standard | remarks |
|--------------|---------------------------|-------------------------------------------------------|---------------------|---------|
| 1 | Single overcharge | Single string protection voltage | 3.7V | Can set |
| | | Overpressure protection delay | 2s.0 | Can set |
| 2 | Single over | Single string protection voltage | 2.5V | Can set |
| | | Over-release protection delay | 2.0s | Can set |
| 3 | Total pressure overcharge | Overpressure protects voltage | 680V | Can set |
| | | Overpressure protection delay | 2.0s | Can set |
| 4 | Total pressure over | Under pressure protection voltage | 460V | Can set |
| | | Default pressure protection delay | 2.0s | Can set |
| 5 | Charging over the flow | Charge overcharge protection value | 150A | Can set |
| | | Charge overcharge delay | 2.0s | Can set |
| 6 | Discharge overflow | Discharge overprotection value | 310A | Can set |
| | | Over-current discharge delay | 2s | Can set |
| 7 | temperature | Battery charging for high temperature protection | 65°C | Can set |
| | | Battery to charge for low-temperature protection | 0°C | Can set |
| | | Battery discharge high temperature protection | 65°C | Can set |
| | | Battery discharge is under low-temperature protection | -10°C | Can set |